

PLACA MOTHERBOARD GIGABYTE H410M H (REV. 1.0) LGA1200, DDR4, , USB 3.2

[Ver producto](#)

- ☑ Supports 10th Gen Intel® Core™ Processors
- ☑ Dual Channel Non-ECC Unbuffered DDR4, 2 DIMMs
- ☑ 8-Channel HD Audio with High Quality Audio Capacitors
- ☑ GIGABYTE Exclusive 8118 Gaming LAN with Bandwidth Management
- ☑ Smart Fan 5 features Multiple Temperature Sensors and Hybrid Fan Headers with FAN STOP
- ☑ GIGABYTE APP Center, Simple and Easy Use
- ☑ Anti-Sulfur Resistors Design

Precio: S/355

[Añadir al carrito](#)



Descripción

?

Procesador

?Support for 10th Generation Intel® Core? i9 processors/Intel® Core? i7 processors/Intel® Core? i5 processors/Intel® Core? i3 processors/Intel® Pentium® processors/Intel® Celeron® processors in the LGA1200 package

?L3 cache varies with CPU

(Please refer "CPU Support List" for more information.)

?

Chipset

?Intel® H410 Express Chipset

?

Memoria

?Intel® Core? i9/i7 processors:

Support for DDR4 2933/2666/2400/2133 MHz memory modules

?Intel® Core? i5/i3/Pentium®/Celeron® processors:

Support for DDR4 2666/2400/2133 MHz memory modules

?2 x DDR4 DIMM sockets supporting up to 64 GB (32 GB single DIMM capacity) of system memory

?Dual channel memory architecture

- ☒ Support for ECC Un-buffered DIMM 1Rx8/2Rx8 memory modules (operate in non-ECC mode)
- ☒ Support for non-ECC Un-buffered DIMM 1Rx8/2Rx8/1Rx16 memory modules
- ☒ Support for Extreme Memory Profile (XMP) memory modules

(Please refer "Memory Support List" for more information.)

☒

Gráficos Integrados

Integrated Graphics Processor-Intel® HD Graphics support:

- ☒ 1 x D-Sub port, supporting a maximum resolution of 1920x1200@60 Hz
 - ☒ 1 x HDMI ports, supporting a maximum resolution of 4096x2160@30 Hz
- * Support for HDMI 1.4 version and HDCP 2.3.

Maximum shared memory of 512 MB

☒

Audio

- ☒ Realtek® audio codec
- ☒ High Definition Audio
- ☒ 2/4/5.1/7.1-channel

* To configure 7.1-channel audio, you need to open the audio software and select Device advanced settings > Playback Device to change the default setting first. Please visit GIGABYTE's website for details on configuring the audio software.

☒

LAN

Realtek® GbE LAN chip (1000 Mbit/100 Mbit)

?

Puertos de Expansión

1 x PCI Express x16 slot, running at x16

2 x PCI Express x1 slots

(The PCI Express slots conform to PCI Express 3.0 standard.)

Supports up to ASPM L1.2 power management protocols.

?

Interfaz de Almacenamiento

1 x M.2 connector (Socket 3, M key, type 2242/2260/2280 SATA and PCIe x2 SSD support)

4 x SATA 6Gb/s connectors

* Refer to "1-7 Internal Connectors," for the installation notices for the M.2 and SATA connectors.

M.2 connectors support up to ASPM L1.2 PCIe power management protocols.

?

USB

Chipset:

- 4 x USB 3.2 Gen 1 ports (2 ports on the back panel, 2 ports available through the internal USB header)
- 6 x USB 2.0/1.1 ports (4 ports on the back panel, 2 ports available through the internal USB header)

?

Conectores Internos de E/S

- 1 x 24-pin ATX main power connector
- 1 x 8-pin ATX 12V power connector
- 1 x CPU fan header
- 1 x system fan header
- 1 x RGB LED strip header
- 4 x SATA 6Gb/s connectors
- 1 x M.2 Socket 3 connector
- 1 x front panel header
- 1 x front panel audio header
- 1 x USB 3.2 Gen 1 header
- 1 x USB 2.0/1.1 header
- 1 x Trusted Platform Module header (For the GC-TPM2.0 SPI/GC-TPM2.0 SPI 2.0 module only)
- 1 x serial port header
- 1 x Clear CMOS jumper

?

Conectores del Panel Trasero

- 1 x PS/2 keyboard/mouse port
- 1 x D-Sub port
- 1 x HDMI port
- 2 x USB 3.2 Gen 1 ports

- 4 x USB 2.0/1.1 ports
- 1 x RJ-45 port
- 3 x audio jacks

?

Controlador de E/S

iTE® I/O Controller Chip

?

Monitorización H/W

- Voltage detection
- Temperature detection
- Fan speed detection
- Overheating warning
- Fan fail warning
- Fan speed control

* Whether the fan speed control function is supported will depend on the cooler you install.

?

BIOS

- 1 x 128 Mbit flash
- Use of licensed AMI UEFI BIOS

☒PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0

☒

Características Únicas

☒Support for APP Center

* Available applications in APP Center may vary by motherboard model. Supported functions of each application may also vary depending on motherboard specifications.

@BIOS

Ambient LED

EasyTune

Fast Boot

Game Boost

ON/OFF Charge

Smart Backup

System Information Viewer

☒Support for Q-Flash

☒Support for Xpress Install

☒

Software Incluido

☒Norton® Internet Security (OEM version)

☒Realtek® 8118 Gaming LAN Bandwidth Control Utility

☒

Sistema Operativo

Support for Windows 10 64-bit

?

Diseño

Micro ATX Form Factor; 22.6cm x 17.4cm

SKU: 348563

Categorías: [PIEZAS DE COMPUTADORA](#), [PLACA MADRE](#)